

# NOMOS GLASHÜTTE

## Data sheet Ahoi neomatik 38 date sand



### CASE

stainless steel, bipartite  
sapphire crystal glass back  
fixed with six screws; screw-down  
crown, crown guard

### GLASS

domed sapphire crystal with anti-  
reflective coating inside and out

### WINDING

automatic

### DIMENSIONS

diameter 38.5 mm  
height 9.9 mm

### WATER RESISTANCE

up to 20 atm  
(suitable for diving)

### DIAL

sand colored, hour indexes with  
white superluminova  
date window at three o'clock

### HANDS

rhodium-plated, with superluminova  
inlay in white  
seconds hand orange

### STRAP

textile strap dark gray, woven,  
waterproof  
lug width 20 mm

### REFERENCE

527



### CALIBER

DUW 6101—in-house built NOMOS  
neomatik caliber with automatic  
winding, neomatik date mechanism,  
and bidirectional quick correction  
feature

### MOVEMENT HEIGHT

3.6 mm

### DIAMETER

14 ½ lines (33.0 mm)

### POWER RESERVE

up to 42 hours

### SPECIAL QUALITIES

patented date mechanism  
NOMOS swing system  
tempered blue balance spring  
NOMOS balance bridge, fixed by  
screws on both sides  
stop-seconds mechanism  
bidirectional winding rotor with  
gold-plated embossing  
Glashütte three-quarter plate  
DUW regulation system  
adjusted in six positions  
27 jewels  
tempered blue screws  
rhodium-plated surfaces with  
Glashütte ribbing and NOMOS  
perlage  
golden engravings