

NOMOS GLASHÜTTE

Data sheet Ahoi neomatik 38 date sky



CASE

stainless steel, bipartite
stainless steel back
fixed with six screws; screw-down
crown, crown guard

GLASS

domed sapphire crystal with anti-
reflective coating inside and out

WINDING

automatic

DIMENSIONS

diameter 38.5 mm
height 9.8 mm

WATER RESISTANCE

up to 20 atm
(suitable for diving)

DIAL

sky blue, hour indexes with white
superluminova
date window at three o'clock

HANDS

rhodium-plated, with superluminova
inlay in white
seconds hand orange

STRAP

textile strap blue-black, woven,
waterproof
lug width 20 mm

REFERENCE

516



CALIBER

DUW 6101—in-house built NOMOS
neomatik caliber with automatic
winding, neomatik date mechanism,
and bidirectional quick correction
feature

MOVEMENT HEIGHT

3.6 mm

DIAMETER

14 ½ lines (33.0 mm)

POWER RESERVE

up to 42 hours

SPECIAL QUALITIES

patented date mechanism
NOMOS swing system
tempered blue balance spring
NOMOS balance bridge, fixed by
screws on both sides
stop-seconds mechanism
bidirectional winding rotor with
gold-plated embossing
Glashütte three-quarter plate
DUW regulation system
adjusted in six positions
27 jewels
tempered blue screws
rhodium-plated surfaces with
Glashütte ribbing and NOMOS
perlage
golden engravings