

# NOMOS GLASHÜTTE

## Data sheet Lambda white gold



**CASE**  
white gold 18 kt, tripartite  
sapphire crystal glass back

**GLASS**  
domed sapphire crystal  
glass with anti-reflective  
coating on inner side

**WINDING**  
manual

**DIMENSIONS**  
diameter 42.0 mm  
height 8.9 mm

**WATER RESISTANCE**  
up to 3 atm  
(splash-proof)

**DIAL**  
galvanized, white silver-  
plated

**HANDS**  
steel, tempered blue

**STRAP**  
Horween Genuine Shell  
Cordovan black, remborde,  
cushioned  
lug width 22 mm

**REFERENCE**  
933



**CALIBER**  
DUW 1001—in-house built  
NOMOS caliber with  
manual winding and power  
reserve indicator

**MOVEMENT HEIGHT**  
3.6 mm

**DIAMETER**  
14 ¼ lines (32 mm)

**POWER RESERVE**  
up to 43 hours

**SPECIAL QUALITIES**  
297° power reserve  
mechanism  
twin mainspring barrels  
stop-seconds mechanism  
hand-engraved balance  
cock  
edges beveled and  
polished by hand  
Glashütte three-quarter  
plate  
screw balance  
adjusted in six positions  
swan neck fine adjustment  
29 jewels, of which six in  
polished and screwed gold  
chatons  
rhodium-plated surfaces  
with fine sunbeam  
polishing and NOMOS  
perlage