

# NOMOS GLASHÜTTE

## Data sheet Ludwig neomatik 41 date



**CASE**  
stainless steel, tripartite  
sapphire crystal glass back

**GLASS**  
sapphire crystal glass with anti-reflective coating on inner side

**WINDING**  
automatic

**DIMENSIONS**  
diameter 40.5 mm  
height 7.7 mm

**WATER RESISTANCE**  
up to 5 atm  
(splash-proof)

**CALIBER**  
DUW 6101—in-house built NOMOS neomatik caliber with automatic winding, neomatik date mechanism, and bidirectional quick correction feature

**MOVEMENT HEIGHT**  
3.6 mm

**DIAMETER**  
15 ½ lines (35.2 mm)

**POWER RESERVE**  
up to 42 hours

**DIAL**  
galvanized, white silver-plated  
date window at three o'clock

**HANDS**  
steel, tempered blue

**STRAP**  
Horween Genuine Shell Cordovan  
black, remborde  
lug width 20 mm

**REFERENCE**  
261



**SPECIAL QUALITIES**  
patented date mechanism  
NOMOS swing system  
tempered blue balance spring  
NOMOS balance bridge, fixed by screws on both sides  
stop-seconds mechanism  
bidirectional winding rotor with gold-plated embossing  
Glashütte three-quarter plate  
DUW regulation system  
adjusted in six positions  
27 jewels  
tempered blue screws  
rhodium-plated surfaces with Glashütte ribbing and NOMOS perlage  
golden engravings