

NOMOS GLASHÜTTE

Data sheet Ludwig neomatik 41 date



CASE

stainless steel, tripartite
sapphire crystal glass back

GLASS

sapphire crystal glass with anti-reflective coating on inner side

WINDING

automatic

DIMENSIONS

diameter 40.5 mm
height 7.7 mm

WATER RESISTANCE

up to 5 atm
(splash-proof)

DIAL

galvanized, white silver-plated
date window at three o'clock, roman numerals

HANDS

steel, tempered blue

STRAP

Horween Genuine Shell Cordovan
black, remborde
lug width 20 mm

REFERENCE

262



CALIBER

DUW 6101—in-house built NOMOS
neomatik caliber with automatic
winding, neomatik date mechanism,
and bidirectional quick correction
feature

MOVEMENT HEIGHT

3.6 mm

DIAMETER

15 ½ lines (35.2 mm)

POWER RESERVE

up to 42 hours

SPECIAL QUALITIES

patented date mechanism
NOMOS swing system
tempered blue balance spring
NOMOS balance bridge, fixed by
screws on both sides
stop-seconds mechanism
bidirectional winding rotor with
gold-plated embossing
Glashütte three-quarter plate
DUW regulation system
adjusted in six positions
27 jewels
tempered blue screws
rhodium-plated surfaces with
Glashütte ribbing and NOMOS
perlage
golden engravings