

NOMOS GLASHÜTTE

Data sheet

Metro date power reserve



CASE
stainless steel
sapphire crystal glass back

GLASS
domed sapphire crystal
glass

WINDING
manual

DIMENSIONS
diameter 37.0 mm
height 7.6 mm

WATER RESISTANCE
up to 3 atm
(splash-proof)

DIAL
galvanized, white silver-plated
mint green indexes at
three, nine and twelve
o'clock

HANDS
oxidized black
seconds hand red

STRAP
Horween Genuine Shell
Cordovan black, with
quick-change spring bars
lug width 18 mm

REFERENCE
1101



CALIBER
DUW 4401—in-house built
NOMOS caliber with
manual winding, date and
power reserve indicator

MOVEMENT HEIGHT
2.8 mm

DIAMETER
14 ¼ lines (32.1 mm)

POWER RESERVE
up to 42 hours

SPECIAL QUALITIES
patented date mechanism
patented power reserve
indicator
NOMOS swing system
tempered blue balance
spring
stop-seconds mechanism
Glashütte stopwork
Glashütte three-quarter
plate
adjusted in six positions
23 jewels
tempered blue screws
rhodium-plated surfaces
with Glashütte ribbing and
NOMOS perlage
ratchet and crown wheel
with Glashütte sunburst