

# NOMOS GLASHÜTTE

## Data sheet

### Metro neomatik 39 silvercut



#### CASE

stainless steel  
sapphire crystal glass back

#### GLASS

domed sapphire crystal  
glass

#### WINDING

automatic

#### DIMENSIONS

diameter 38.5 mm  
height 8.3 mm

#### WATER RESISTANCE

up to 5 atm  
(suitable for showering)

#### DIAL

rhodium-plated, with  
brushed finish, red indexes  
at three, nine and twelve  
o'clock

#### HANDS

rhodium-plated  
seconds hand red

#### STRAP

Horween Genuine Shell  
Cordovan black, remborde,  
with quick-change spring  
bars  
lug width 19 mm

#### REFERENCE

1114



#### CALIBER

DUW 3001—in-house built  
NOMOS neomatik caliber  
with automatic winding

#### MOVEMENT HEIGHT

3.2 mm

#### DIAMETER

12 ¾ lines (28.8 mm)

#### POWER RESERVE

up to 43 hours

#### SPECIAL QUALITIES

NOMOS swing system  
tempered blue balance  
spring  
NOMOS balance bridge,  
fixed by screws on both  
sides  
stop-seconds mechanism  
bidirectional winding rotor  
Glashütte three-quarter  
plate  
DUW regulation system  
adjusted in six positions  
27 jewels  
tempered blue screws  
rhodium-plated surfaces  
with Glashütte ribbing and  
NOMOS perlage