

NOMOS GLASHÜTTE

Data sheet Metro neomatik 41 Update



CASE

stainless steel, bipartite
sapphire crystal glass back

GLASS

domed sapphire crystal glass

WINDING

automatic

DIMENSIONS

diameter 40.5 mm
height 9.1 mm

WATER RESISTANCE

up to 5 atm
(splash-proof)

DIAL

galvanized, white silver-plated,
indexes at three, nine and twelve
o'clock
date ring
patented date display

HANDS

oxidized black

STRAP

textile strap dark gray, woven,
waterproof, with quick-change
spring bars
lug width 20 mm

REFERENCE

1165



CALIBER

DUW 6101—in-house built NOMOS
neomatik caliber with automatic
winding, neomatik date mechanism,
and bidirectional quick correction
feature

MOVEMENT HEIGHT

3.6 mm

DIAMETER

15 ½ lines (35.2 mm)

POWER RESERVE

up to 42 hours

SPECIAL QUALITIES

patented date mechanism
NOMOS swing system
tempered blue balance spring
NOMOS balance bridge, fixed by
screws on both sides
stop-seconds mechanism
bidirectional winding rotor with
gold-plated embossing
Glashütte three-quarter plate
DUW regulation system
adjusted in six positions
27 jewels
tempered blue screws
rhodium-plated surfaces with
Glashütte ribbing and NOMOS
perlage
golden engravings