

# NOMOS GLASHÜTTE

## Data sheet

### Orion neomatik 39 new black



#### CASE

stainless steel, tripartite  
domed sapphire crystal glass back

#### GLASS

domed sapphire crystal glass with  
anti-reflective coating on inner side

#### WINDING

automatic

#### DIMENSIONS

diameter 38.5 mm  
height 8.7 mm

#### WATER RESISTANCE

up to 5 atm

#### DIAL

galvanized, black  
stamped indexes, diamond-polished,  
rhodium-plated

#### HANDS

rhodium-plated

#### STRAP

Horween Genuine Shell Cordovan  
black, remborde  
lug width 19 mm

#### REFERENCE

346



#### CALIBER

DUW 3001—in-house built NOMOS  
neomatik caliber with automatic  
winding

#### MOVEMENT HEIGHT

3.2 mm

#### DIAMETER

12  $\frac{3}{4}$  lines (28.8 mm)

#### POWER RESERVE

up to 43 hours

#### SPECIAL QUALITIES

NOMOS swing system  
tempered blue balance spring  
NOMOS balance bridge, fixed by  
screws on both sides  
stop-seconds mechanism  
bidirectional winding rotor  
Glashütte three-quarter plate  
DUW regulation system  
adjusted in six positions  
27 jewels  
tempered blue screws  
rhodium-plated surfaces with  
Glashütte ribbing and NOMOS  
perlage