

NOMOS GLASHÜTTE

Data sheet Orion neomatik 39



CASE

stainless steel, tripartite
domed sapphire crystal
glass back

GLASS

domed sapphire crystal
glass with anti-reflective
coating on inner side

WINDING

automatic

DIMENSIONS

diameter 38.5 mm
height 8.6 mm

WATER RESISTANCE

up to 5 atm
(suitable for showering)

CALIBER

DUW 3001—in-house built
NOMOS neomatik caliber
with automatic winding

MOVEMENT HEIGHT

3.2 mm

DIAMETER

12 $\frac{3}{4}$ lines (28.8 mm)

POWER RESERVE

up to 43 hours

DIAL

galvanized, white silver-
plated
stamped indexes,
diamond-polished, gold

HANDS

tempered blue

STRAP

Horween Genuine Shell
Cordovan black, remborde
lug width 19 mm

REFERENCE

340

SPECIAL QUALITIES

NOMOS swing system
tempered blue balance
spring
NOMOS balance bridge,
fixed by screws on both
sides
stop-seconds mechanism
bidirectional winding rotor
Glashütte three-quarter
plate
DUW regulation system
adjusted in six positions
27 jewels
tempered blue screws
rhodium-plated surfaces
with Glashütte ribbing and
NOMOS perlage