

NOMOS GLASHÜTTE

Data sheet Orion neomatik 39



CASE

stainless steel, tripartite
domed sapphire crystal glass back

GLASS

domed sapphire crystal glass with
anti-reflective coating on inner side

WINDING

automatic

DIMENSIONS

diameter 38.5 mm
height 8.7 mm

WATER RESISTANCE

up to 5 atm
(splash-proof)

DIAL

galvanized, white silver-plated
stamped indexes, diamond-polished,
gold

HANDS

tempered blue

STRAP

Horween Genuine Shell Cordovan
black, remborde
lug width 19 mm

REFERENCE

340



CALIBER

DUW 3001—in-house built NOMOS
neomatik caliber with automatic
winding

MOVEMENT HEIGHT

3.2 mm

DIAMETER

12 $\frac{3}{4}$ lines (28.8 mm)

POWER RESERVE

up to 43 hours

SPECIAL QUALITIES

NOMOS swing system
tempered blue balance spring
NOMOS balance bridge, fixed by
screws on both sides
stop-seconds mechanism
bidirectional winding rotor
Glashütte three-quarter plate
DUW regulation system
adjusted in six positions
27 jewels
tempered blue screws
rhodium-plated surfaces with
Glashütte ribbing and NOMOS
perlage