

NOMOS

GLASHÜTTE

Data sheet

Orion neomatik 39 white



CASE

stainless steel, tripartite
domed sapphire crystal
glass back

GLASS

domed sapphire crystal
glass with anti-reflective
coating on inner side

WINDING

automatic

DIMENSIONS

diameter 38.5 mm
height 8.6 mm

WATER RESISTANCE

up to 5 atm
(suitable for showering)

DIAL

galvanized, white silver-
plated
stamped indexes,
diamond-polished, white

HANDS

polished and rhodium-
plated

STRAP

Horween Genuine Shell
Cordovan black, remborde
lug width 19 mm

REFERENCE

341



CALIBER

DUW 3001—in-house built
NOMOS neomatik caliber
with automatic winding

MOVEMENT HEIGHT

3.2 mm

DIAMETER

12 $\frac{3}{4}$ lines (28.8 mm)

POWER RESERVE

up to 43 hours

SPECIAL QUALITIES

NOMOS swing system
tempered blue balance
spring
NOMOS balance bridge,
fixed by screws on both
sides
stop-seconds mechanism
bidirectional winding rotor
Glashütte three-quarter
plate
DUW regulation system
adjusted in six positions
27 jewels
tempered blue screws
rhodium-plated surfaces
with Glashütte ribbing and
NOMOS perlage