

# NOMOS GLASHÜTTE

## Data sheet Orion neomatik



### CASE

stainless steel, tripartite  
domed sapphire crystal glass back

### GLASS

domed sapphire crystal glass

### WINDING

automatic

### DIMENSIONS

diameter 36.4 mm  
height 8.5 mm

### WATER RESISTANCE

up to 5 atm  
(splash-proof)

### DIAL

galvanized, white silver-plated  
minute markers cyan blue

### HANDS

oxidized black  
seconds hand red

### STRAP

Horween Genuine Shell Cordovan  
black, remborde  
lug width 18 mm

### REFERENCE

392



### CALIBER

DUW 3001—in-house built NOMOS  
neomatik caliber with automatic  
winding

### MOVEMENT HEIGHT

3.2 mm

### DIAMETER

12  $\frac{3}{4}$  lines (28.8 mm)

### POWER RESERVE

up to 43 hours

### SPECIAL QUALITIES

NOMOS swing system  
tempered blue balance spring  
NOMOS balance bridge, fixed by  
screws on both sides  
stop-seconds mechanism  
bidirectional winding rotor  
Glashütte three-quarter plate  
DUW regulation system  
adjusted in six positions  
27 jewels  
tempered blue screws  
rhodium-plated surfaces with  
Glashütte ribbing and NOMOS  
perlage