

NOMOS GLASHÜTTE

Data sheet Tangente 2date



CASE

stainless steel, bipartite
sapphire crystal glass back

GLASS

sapphire crystal glass with anti-reflective coating (front and back)

WINDING

manual

DIMENSIONS

diameter 37.5 mm
height 6.8 mm

WATER RESISTANCE

up to 5 atm
(splash-proof)

DIAL

galvanized, white silver-plated
two date displays: date ring and
date window at six o'clock red

HANDS

rhodium-plated

STRAP

Horween Genuine Shell Cordovan
black
lug width 19 mm

REFERENCE

135



CALIBER

DUW 4601—in-house built NOMOS
caliber with manual winding and a
quick-set date function

MOVEMENT HEIGHT

2.8 mm

DIAMETER

15 1/3 lines (34.6 mm)

POWER RESERVE

up to 52 hours

SPECIAL QUALITIES

patented date mechanism
NOMOS-Swing-System
blued balance spring
skeletonized balance cock
stop-seconds mechanism
Glashütte three-quarter plate
DUW regulation system
adjusted in six positions
23 jewels
tempered blue screws
rhodium-plated surfaces with fine
sunbeam ribbing and NOMOS
perlage
Glashütte sunburst on ratchet and
crown wheel
gold-plated engravings