

# NOMOS GLASHÜTTE

## Data sheet

## Tangente neomatik 41 Update



**CASE**  
stainless steel, bipartite  
sapphire crystal glass back

**GLASS**  
sapphire crystal glass with  
anti-reflective coating

**WINDING**  
automatic

**DIMENSIONS**  
diameter 40.5 mm  
height 7.9 mm

**WATER RESISTANCE**  
up to 5 atm  
(suitable for showering)

**DIAL**  
galvanized, white silver-  
plated  
date ring

**HANDS**  
oxidized black

**STRAP**  
Horween Genuine Shell  
Cordovan black, remborde  
lug width 20 mm

**REFERENCE**  
180



**CALIBER**  
DUW 6101—in-house built  
NOMOS neomatik caliber  
with automatic winding,  
neomatik date mechanism,  
and bidirectional quick  
correction feature

**MOVEMENT HEIGHT**  
3.6 mm

**DIAMETER**  
15 ½ lines (35.2 mm)

**POWER RESERVE**  
up to 42 hours

**SPECIAL QUALITIES**  
NOMOS swing system  
tempered blue balance  
spring  
NOMOS balance bridge,  
fixed by screws on both  
sides  
stop-seconds mechanism  
bidirectional winding rotor  
with gold-plated  
embossing  
Glashütte three-quarter  
plate  
DUW regulation system  
adjusted in six positions  
27 jewels  
tempered blue screws  
rhodium-plated surfaces  
with Glashütte ribbing and  
NOMOS perlage  
golden engravings