

# NOMOS

## GLASHÜTTE

### Data sheet

### Tangente neomatik



**CASE**  
stainless steel  
sapphire crystal glass back

**GLASS**  
sapphire crystal glass

**WINDING**  
automatic

**DIMENSIONS**  
diameter 35.0 mm  
height 6.9 mm

**WATER RESISTANCE**  
up to 3 atm  
(splash-proof)

**DIAL**  
galvanized, white silver-plated  
minute markers cyan blue

**HANDS**  
oxidized black  
seconds hand red

**STRAP**  
Horween Genuine Shell Cordovan  
black, remborde  
lug width 18 mm

**REFERENCE**  
175



**CALIBER**  
DUW 3001—in-house built NOMOS  
neomatik caliber with automatic  
winding

**MOVEMENT HEIGHT**  
3.2 mm

**DIAMETER**  
12  $\frac{3}{4}$  lines (28.8 mm)

**POWER RESERVE**  
up to 43 hours

**SPECIAL QUALITIES**  
NOMOS swing system  
tempered blue balance spring  
NOMOS balance bridge, fixed by  
screws on both sides  
stop-seconds mechanism  
bidirectional winding rotor  
Glashütte three-quarter plate  
DUW regulation system  
adjusted in six positions  
27 jewels  
tempered blue screws  
rhodium-plated surfaces with  
Glashütte ribbing and NOMOS  
perlage