

NOMOS GLASHÜTTE

Data sheet

Tetra neomatik 39 silvercut



CASE
stainless steel
sapphire crystal glass back

GLASS
sapphire crystal glass with
anti-reflective coating on
inner side

WINDING
automatic

DIMENSIONS
size 33.0 x 33.00 mm
height 7.3 mm

WATER RESISTANCE
up to 3 atm
(splash-proof)

DIAL
rhodium-plated, with
brushed finish

HANDS
steel, tempered blue
seconds hand red

STRAP
Horween Genuine Shell
Cordovan black, remborde
lug width 20 mm

REFERENCE
423



CALIBER
DUW 3001—in-house built
NOMOS neomatik caliber
with automatic winding

MOVEMENT HEIGHT
3.2 mm

DIAMETER
12 3/4 lines (28.8 mm)

POWER RESERVE
up to 43 hours

SPECIAL QUALITIES
NOMOS swing system
tempered blue balance
spring
NOMOS balance bridge,
fixed by screws on both
sides
stop-seconds mechanism
bidirectional winding rotor
Glashütte three-quarter
plate
DUW regulation system
adjusted in six positions
27 jewels
tempered blue screws
rhodium-plated surfaces
with Glashütte ribbing and
NOMOS perlage