

NOMOS

GLASHÜTTE

Data sheet

Zürich Worldtimer



CASE

stainless steel, tripartite
sapphire crystal glass back
fixed with six screws

GLASS

domed sapphire crystal with anti-reflective coating inside and out

WINDING

automatic

DIMENSIONS

diameter 39.9 mm
height 10.9 mm

WATER RESISTANCE

up to 3 atm
(splash-proof)

DIAL

galvanized, white, with world time
and 24-hour indicator

HANDS


rhodium-plated, faceted

STRAP

Horween Genuine Shell Cordovan
black
lug width 20 mm

REFERENCE

805



CALIBER

DUW 5201—in-house built NOMOS
caliber with automatic winding,
worldtime and 24-hour indicator

MOVEMENT HEIGHT

5.7 mm

DIAMETER

13 $\frac{3}{4}$ lines (31 mm)

POWER RESERVE

up to 42 hours

SPECIAL QUALITIES

worldtime mechanism
NOMOS swing system
tempered blue balance spring
stop-seconds mechanism
Glashütte stopwork
bidirectional winding rotor
Glashütte three-quarter plate
DUW regulation system
adjusted in six positions
26 jewels
tempered blue screws
rhodium-plated surfaces with
Glashütte ribbing and NOMOS
perlage
ratchet and duplex wheel with
Glashütte sunburst