

NOMOS GLASHÜTTE

Data sheet Ahoi neomatik



CASE

stainless steel
sapphire crystal glass back
fixed with six screws;
screw-down crown, crown
guard

GLASS

domed sapphire crystal
glass

WINDING

automatic

DIMENSIONS

diameter 36.3 mm
height 9.6 mm

WATER RESISTANCE

up to 20 atm
(suitable for diving)

DIAL

galvanized, white silver-
plated, hour indexes with
white superluminova

HANDS

rhodium-plated, with
superluminova inlay in light
blue
seconds hand neon orange

STRAP

textile strap light gray,
woven, waterproof
lug width 18 mm

REFERENCE

560



CALIBER

DUW 3001—in-house built
NOMOS neomatik caliber
with automatic winding

MOVEMENT HEIGHT

3.2 mm

DIAMETER

12 ¾ lines (28.8 mm)

POWER RESERVE

up to 43 hours

SPECIAL QUALITIES

NOMOS swing system
tempered blue balance
spring
NOMOS balance bridge
stop-seconds mechanism
bidirectional winding rotor
Glashütte three-quarter
plate
DUW regulation system
adjusted in six positions
27 jewels
tempered blue screws
rhodium-plated surfaces
with Glashütte ribbing and
NOMOS perlage