

# NOMOS GLASHÜTTE

## Data sheet Ahoi



**CASE**  
stainless steel  
sapphire crystal glass back  
fixed with six screws;  
screw-down crown, crown  
guard

**GLASS**  
domed sapphire crystal  
glass

**WINDING**  
automatic

**DIMENSIONS**  
diameter 40.3 mm  
height 10.6 mm

**WATER RESISTANCE**  
up to 20 atm  
(suitable for diving)

**DIAL**  
galvanized, white silver-  
plated, hour indexes with  
white superluminova

**HANDS**  
rhodium-plated, with  
superluminova inlay in light  
blue  
seconds hand neon orange

**STRAP**  
blue-black textile strap,  
woven, waterproof  
lug width 20 mm

**REFERENCE**  
550



**CALIBER**  
DUW 5001—in-house built  
NOMOS caliber with  
automatic winding

**MOVEMENT HEIGHT**  
4.3 mm

**DIAMETER**  
13 ¾ lines (31 mm)

**POWER RESERVE**  
up to 43 hours

**SPECIAL QUALITIES**  
NOMOS swing system  
tempered blue balance  
spring  
stop-seconds mechanism  
Glashütte stopwork  
bidirectional winding rotor  
Glashütte three-quarter  
plate  
adjusted in six positions  
26 jewels  
tempered blue screws  
rhodium-plated surfaces  
with Glashütte ribbing and  
NOMOS perlage  
ratchet and duplex wheel  
with Glashütte sunburst