

NOMOS GLASHÜTTE

Data sheet

Ludwig neomatik 41 date



CASE

stainless steel, tripartite
sapphire crystal glass back

GLASS

sapphire crystal glass with
anti-reflective coating on
inner side

WINDING

automatic

DIMENSIONS

diameter 40.5 mm
height 7.7 mm

WATER RESISTANCE

up to 5 atm
(suitable for showering)

DIAL

galvanized, white silver-
plated
date window at three
o'clock

HANDS

steel, tempered blue

STRAP

Horween Genuine Shell
Cordovan black, remborde
lug width 20 mm

REFERENCE

261



CALIBER

DUW 6101—in-house built
NOMOS neomatik caliber
with automatic winding,
neomatik date mechanism,
and bidirectional quick
correction feature

MOVEMENT HEIGHT

3.6 mm

DIAMETER

15 ½ lines (35.2 mm)

POWER RESERVE

up to 42 hours

SPECIAL QUALITIES

NOMOS swing system
tempered blue balance
spring
NOMOS balance bridge,
fixed by screws on both
sides
stop-seconds mechanism
bidirectional winding rotor
with gold-plated
embossing
Glashütte three-quarter
plate
DUW regulation system
adjusted in six positions
27 jewels
tempered blue screws
rhodium-plated surfaces
with Glashütte ribbing and
NOMOS perlage
golden engravings