

# NOMOS GLASHÜTTE

## Data sheet Metro 38



**CASE**  
stainless steel  
sapphire crystal glass back

**GLASS**  
domed sapphire crystal  
glass

**WINDING**  
manual

**DIMENSIONS**  
diameter 38.5 mm  
height 7.7 mm

**WATER RESISTANCE**  
up to 3 atm  
(splash-proof)

**CALIBER**  
Alpha—in-house built  
NOMOS caliber with  
manual winding

**MOVEMENT HEIGHT**  
2.6 mm

**DIAMETER**  
10 ½ lines (23.3 mm)

**POWER RESERVE**  
up to 43 hours

**DIAL**  
galvanized, white silver-  
plated, blue indexes at  
three, six, nine and twelve  
o'clock

**HANDS**  
oxidized black  
seconds hand red

**STRAP**  
Horween Genuine Shell  
Cordovan black, with  
quick-change spring bars  
lug width 19 mm

**REFERENCE**  
1108

**SPECIAL QUALITIES**  
stop-seconds mechanism  
Glashütte stopwork  
Glashütte three-quarter  
plate  
adjusted in six positions  
17 jewels  
tempered blue screws  
rhodium-plated surfaces  
with Glashütte ribbing and  
NOMOS perlage  
ratchet and crown wheel  
with Glashütte sunburst