

NOMOS GLASHÜTTE

Data sheet Metro neomatik 39



CASE
stainless steel
sapphire crystal glass back

GLASS
domed sapphire crystal
glass

WINDING
automatic

DIMENSIONS
diameter 38.5 mm
height 8.3 mm

WATER RESISTANCE
up to 5 atm
(suitable for showering)

CALIBER
DUW 3001—in-house built
NOMOS neomatik caliber
with automatic winding

MOVEMENT HEIGHT
3.2 mm

DIAMETER
12 $\frac{3}{4}$ lines (28.8 mm)

POWER RESERVE
up to 43 hours

DIAL
galvanized, white silver-
plated, gray indexes at
three, nine and twelve
o'clock

HANDS
oxidized black
seconds hand red

STRAP
Horween Genuine Shell
Cordovan black, remborde,
with quick-change spring
bars
lug width 19 mm

REFERENCE
1113

SPECIAL QUALITIES
NOMOS swing system
tempered blue balance
spring
NOMOS balance bridge,
fixed by screws on both
sides
stop-seconds mechanism
bidirectional winding rotor
Glashütte three-quarter
plate
DUW regulation system
adjusted in six positions
27 jewels
tempered blue screws
rhodium-plated surfaces
with Glashütte ribbing and
NOMOS perlage